

General Info



ID	#3
Product Name	HSAW Line Pipes
Slogan	With the quality and dedication to meet the needs of our business partners in the best way
Description	We produce Spiral Welded Pipes from our production line, which has many coating options such as epoxy, polyethylene, and polypropylene, with the quality and dedication to meet the needs of our business partners in the best way.
Category	Energy

Product Info

Sizes

Outside Diameter
508 mm - 3.048 mm
20'' - 120''

Wall Thickness
5,16 mm - 25,4 mm
0,203'' - 1,000''

Length
Single lengths up to 24,50 m*

* For pilling pipes single lengths up to 55 m

Production Standards & Material Qualities

API 5L	PSL1 - PSL2 GRA - X80 (N, M)	CSA Z245.1 : Requirement of category I,
II, III		
ISO 3183	L555 - X80 (N, M, ME)	

Coating Standards

- Abrasion Resistant Overlay (ARO) OD Coating: API 5L7, CSA Z245.20, NACE RP 0394, AWWA C213
- FBE (Fusion Bonded Epoxy) OD Coating: API 5L7, CSA Z245.20, NACE RP 0394, AWWA C213
- Polyethylene OD Coating: DIN 30670, TS 5139, NF A 49-710, UNI 9099, EN ISO 21809-1
- Polypropylene OD Coating: DIN 30678, NF A 49-711, EN ISO 21809-1
- Flowcoat Epoxy ID Coating: API RP 5L2, EN 10301
- Solvent Free Epoxy (SFE) ID Coating: AWWA C 210
- Glass fibre reinforced plastic GRP OD Coating

Quality Certificates

- API 5L
- API Q1
- ISO9001
- ISO14001
- ISO45001
- EN ISO/IEC 17025
- EN ISO 3183

Production Range

