

## General Info



|                     |  |
|---------------------|--|
| <b>ID</b>           | #9   |
| <b>Product Name</b> | Water Well Casing Pipes  |
| <b>Slogan</b>       | With the quality and dedication to meet the needs of our business partners in the best way |
| <b>Description</b>  |  |
| <b>Category</b>     | Water  |

## Product Info

|              |
|--------------|
| <b>Sizes</b> |
|--------------|

**Outside Diameter**  
**33,4 mm - 323,9 mm**  
**1,314'' - 12,751''**

**Wall Thickness**  
**3,2 mm - 9,5 mm**  
**0,126'' - 0,374''**

**Length**  
**6,00 m - 18,30 m**  
**19,68 ft - 60 ft**

---

#### **Production Standards & Material Qualities**

- **ASTM A 589 Type I, II, III, IV Production Standard**
- **ASTM A 53**
- **Reliable High Steel Quality**
- **From Grade A or Grade B Material Quality**
- **Weldable**
- **Threadable**

---

#### **Tests & Certificates**

- **Visual and Dimensional Inspection**
  - **Leak tightness testing: Hydrostatic Test, Eddy Current Test**
  - **Destructive Tests: Flattening, Bending**
  - **Mechanical Tests**
  - **Chemical Analysis**
  - **Metallographic Examination**
  - **Others, as required by the standards**
  - **Mill Test Certificates**
    - **Issued upon request according to**  
**EN 10204 2.1; 2.2; 3.1; 3.2**
  - **NDT Standards:**
    - **ET (EN ISO 10893-2), ET (ASTM E309)**
  - **Glass fiber reinforced plastic (GRP), OD Coating**
-

|                             |
|-----------------------------|
| <b>Finishing Operations</b> |
|-----------------------------|

- |   |
|---|
| <ul style="list-style-type: none"><li>• Threaded Option up to 6”</li><li>• Hot Dip Galvanised Option up to 6”</li></ul> |
|---|

---

|                        |
|------------------------|
| <b>Product Options</b> |
|------------------------|

